



FEATURES A UNIQUE SWING FRAME DESIGN

Easily access your rackmount gear from the rear once mounted on wall.

Features and Benefits

- 19" Swing Frames Enclosures manufactured to precise dimensions and are made from SPCC High quality cold roll steel with a thickness of 2.0mm for mounting rails and 1.2mm for other areas
- Sturdy welded frame IP20 - IP30 construction.
- Epoxy polyester powder paint over a degreased and phosphoric acidation surface treatment with a textured finish.
- Enclosure colour - Midnight Grey.
- Complies to ANSI/EIARS-310-D, IEC297-2, DIN41491, DIN41494, Part7,GB/T3047.2-92 Standards.
- The front door with glass panel
 - > contains a full tempered safety glass panel.
 - > the glass panel provides an un-obstructed view on installed equipment.
 - > the glass panel alleviates static electricity interference with installed equipment.
 - > has quick release hinges that allows for simple demounting.
 - > can be easily re-hinged to the left hand side of the enclosure.
 - > is fitted with earth continuity leads between enclosure and door
 - > has a keyed lock.
- Side Access panels are easily demountable and have a keyed lock.
- Swing frame has a keyed lock.
- The internal side rails are depth adjustable.
- Each swing frame is supplied a set of two (2) 125mm cooling fans to extract hot air from the interior.
- RU positions are marked and notched simplifying equipment alignment.
- Generous cable access glands are provided in the top rear and bottom rear of the enclosure gland in the folding section.

ENCLOSURES

Supply Includes

- 1 x Basic housing
- 1 x 5mm Glazed safety glass door with security panel & lock
- 2 x Side panels with cam lock
- 2 x Top gland plate
- 1 x Bottom gland plate
- 4 x 19" Mounting rails
- 1 x Pre-installed 6 Way Power board
- 2 x 125mm Ceiling Cooling Fans
- Pack of 20 cage nuts and screws
- 2 Front door keys
- 2 Swing frame keys

* Each key set has a different pattern.

Part Codes & Rack Dimensions

PART NO	DESCRIPTION	RACK DIMENSIONS (mm)			
		RU Height	Width	Depth	Height
SFE9RU	Swing Frame Enclosure 9RU 551W 523D 500H	9RU	600	705	501
SFE12RU	Swing Frame Enclosure 12RU 551W 523D 625H	12RU	600	705	635
SFE18RU	Swing Frame Enclosure 18RU 551W 523D 900H	18RU	600	705	900

NEW! 400mm Deep Coming Soon!

PART NO	DESCRIPTION	RACK DIMENSIONS (mm)			
		RU Height	Width	Depth	Height
SFE9RU - 4	Swing Frame Enclosure 9RU 551W 523D 500H	9RU	600	505	501
SFE12RU - 4	Swing Frame Enclosure 12RU 551W 523D 625H	12RU	600	505	635
SFE18RU - 4	Swing Frame Enclosure 18RU 551W 523D 900H	18RU	600	505	900



SFE9RU



SFE9RU - 4

ENCLOSURES

Optional Extras



Cantilever Shelf 19"
Mounts to front of rack only

R19CS300 - 300mm Deep

R19CS400 - 400mm Deep



19" 10 way Horizontal Power Rail

R1910HPR



Cable Management

R19PCM1RU - 1RU patch cord minder

R19PCM2RU - 2RU patch cord minder

M6 Cagenut Screws
(pack of 40 cagenuts and screws)

CAGENUT-40



Patch Lead Manager

R19PCM - 19" 1RU patch lead manager

Blanking Panels to cover empty RU Spaces

R19BP1RU 1RU Blank

R19BP2RU 2RU Blank

R19VP1RU 1RU Vented

R19VP2RU 2RU Vented



Fixed Trays

R19FT400 Suitable for
600mm Deep Cabinet

R19FT700 Suitable for
900mm Deep Cabinet

R19FT600 Suitable for
800mm Deep Cabinet

R19FT800 Suitable for
1000mm Deep Cabinet



For further information, call your account manager or visit www.legendwebshop.com
Phone - 1800 3282 00 OR (1800 DATA 00) | Fax - 1800 3282 39 OR (1800 DATA FX)

