



Features and Benefits

- 19" Wall Mount Enclosure is manufactured to precise dimensions and is made from SPCC High quality cold roll steel with a thickness of 2.0mm for mounting rails and 1.2mm for other areas.
- Sturdy welded frame IP20 - IP30 construction.
- Epoxy polyester powder paint over a degreased and phosphoric acidation surface treatment with a textured finish.
- Enclosure colour - Midnight Grey.
- Complies to ANSI/EIARS-310-D, IEC297-2, DIN41491, DIN41494, Part7,GB/T3047.2-92 Standards.
- The front door;
 - > contains a full tempered safety glass panel.
 - > the glass panel provides an un-obstructed view on installed equipment.
 - > the glass panel alleviates static electricity interference with installed equipment.
 - > has quick release hinges that allows for simple demounting.
 - > can be easily re-hinged to the left hand side of the enclosure.
 - > is fitted with earth continuity leads between enclosure and door.
 - > has a keyed lock.
 - > have rear cut out on wall mounts.
- Side Access panels are easily demountable and have a keyed lock.
- The internal side rails are depth adjustable.
- Each Wall Mount Enclosure is supplied a set of two (2) 125mm cooling fans to extract hot air from the interior.
- RU positions are marked and notched simplifying equipment alignment.
- Generous cable access glands are provided in the top rear and bottom rear of the enclosure.

ENCLOSURES

Rack Configuration

- 1 x Basic housing
- 1 x 5mm Glazed safety glass door with security panel & Lock
- 2 x Side panels with Cam lock
- 1 x Top Gland plate
- 1 x Bottom Gland plate
- 4 x 19" Mounting rails
- 1 x Pre-installed 6 Way Power board
- 2 x 125mm Ceiling Cooling Fans
- Pack of 20 cage nuts and screws
- 2 Front door keys

* Each key set has a different pattern.

Part Codes & Rack Dimensions

PART NO	DESCRIPTION	RACK DIMENSIONS (mm)			
		RU Height	Width	Depth	Height
WME6RU	Wall Mount Enclosure 6RU 600W 600D 368H	6RU	600	600	368
WME6RU-4	Wall Mount Enclosure 6RU 600W 400D 368H	6RU	600	400	368
WME9RU	Wall Mount Enclosure 9RU 600W 600D 501H	9RU	600	600	501
WME12RU	Wall Mount Enclosure 12RU 600W 600D 635H	12RU	600	600	635
WME12RU-4	Wall Mount Enclosure 12RU 600W 400D 635H	12RU	600	400	635
WME18RU	Wall Mount Enclosure 18RU 600W 600D 900H	18RU	600	600	900



WME12RU



WME12RU - 4

ENCLOSURES

Optional Extras



Cantilever Shelf 19"
Mounts to front of rack only

R19CS300 - 300mm Deep

R19CS400 - 400mm Deep



19" 10 way Horizontal Power Rail

R1910HPR



Cable Management

R19PCM1RU - 1RU patch cord minder

R19PCM2RU - 2RU patch cord minder

M6 Cagenut Screws
(pack of 40 cagenuts and screws)

CAGENUT-40



Patch Lead Manager

R19PCM - 19" 1RU patch lead manager

Blanking Panels to cover empty RU Spaces

R19BP1RU 1RU Blank

R19BP2RU 2RU Blank

R19VP1RU 1RU Vented

R19VP2RU 2RU Vented



Fixed Trays

R19FT400 Suitable for
600mm Deep Cabinet

R19FT700 Suitable for
900mm Deep Cabinet

R19FT600 Suitable for
800mm Deep Cabinet

R19FT800 Suitable for
1000mm Deep Cabinet



For further information, call your account manager or visit www.legendwebshop.com
Phone - 1800 3282 00 OR (1800 DATA 00) | Fax - 1800 3282 39 OR (1800 DATA FX)

LEGEND
Performance Technology