

P1166P DLP SVGA (EY.J9501.009)

Acer P1166P combines extra portability and excellent colour reproduction to form the ultimate presentation tool. The Acer P1166P is well suited for the most demanding Multimedia presentation applications.

Features :

- Projection System: DLP™
- Resolution: Native SVGA (800 x 600)
- Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
- Computer Compatibility: IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
- Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
- Aspect Ratio: 4:3 (Native), 16:9
- Contrast Ratio: 2700:1
- Displayable Colors: 134 Million Colors
- Brightness: 2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
- Projection Lens: F = 2.41 ~ 2.66, f = 18.17mm ~ 21.81mm, 1:1.2 Manual Zoom and Manual Focus
- Projection Screen Size: 26" (65cm) ~ 300" (762cm)
- Projection Distance: 3.3' (1.0m) ~ 32.0' (9.8m)
- Throw Ratio: 62"@2m (1.60 ~ 1.92:1)
- Lamp Type/ Life: Osram 180 W user replaceable P-VIP lamp / 3,000 Hours (Standard), 4,000 Hours (ECO)
- Keystone Correction: +/-40 Degrees (Vertical)
- Audio: One Internal Speaker with 2 watts Output
- Weight: 5.5 lbs (2.5 Kg)
- Dimension: 269 x 206 x 96 mm (10.6" x 8.1" x 3.8")
- Operating Temperature: 5°C ~ 35°C / 41°F ~ 95°F
- Noise Level: 30 dBA (Standard mode), 25 dBA (ECO mode)