



DES-1024D

The DES-1024D switch provides 24 auto-sensing 10/100Mbps ports in a desktop box. The switch allows mix and match of Ethernet and Fast Ethernet in full- and half-duplex modes.

24-Port 10/100Mbps Switch for Workgroup

The DES-1024D is an unmanaged 10/100Mbps switch designed to enhance workgroup performance while providing a high level of flexibility. Powerful yet easy to use, this device allows users to simply plug any port to either a 10Mbps or 100Mbps network to multiply bandwidths, boost response time and satisfy heavy load demands.

24 Auto-sensing 10/100Mbps Ports

The switch comes with 24 10/100Mbps ports, allowing a small workgroup to flexibly integrate to Ethernet and Fast Ethernet. These intelligent ports detect the network speed and auto-negotiate between 10BASE-TX and 10BASE-T, as well as between full and half-duplex.

Flow Control for Secure Transmission

All ports support flow control. This function minimizes dropped packets by sending out collision signals when the port's receiving buffer is full.

Auto-negotiation of MDI/MDIX Cross Over

All ports support auto-negotiation of MDI/MDIX cross over. This eliminates the need for cross over cables or uplink ports. Any port can simply plug to a server, a hub or a switch, using the usual straight-through twisted-pair cable.

Plug-and-Play

With 24 plug-and-play ports, the switch is a perfect choice for workgroups to upgrade performance in a client/server environment. The ports can be connected to servers in full-duplex, or hubs in half-duplex.

Direct Connection to Workstations

With low-cost connection per-port, the switch can be set up for direct connection from the PCs. This relieves data bottleneck by giving each workstation a dedicated bandwidth on the network.

Features

- 24 10/100Mbps ports
- Auto MDI/MDIX for each port
- Full/half-duplex support for each port
- Flow control for protection against data loss for each port
- Auto-learning of network configuration
- Secure store-and-forward switching scheme
- Per-port auto-correction of reverse twisted-pair polarity
- Compact desktop size

DES-1024D

Technical Specifications

10/100Mbps Unmanaged Switch

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Protocol

CSMA/CD

Data Transfer Rates

- Ethernet:
 - 10Mbps (half-duplex)
 - 20Mbps (full-duplex)
- Fast Ethernet:
 - 100Mbps (half-duplex)
 - 200Mbps (full-duplex)

Topology

Star

Network Cables

- 10BASE-T:
 - UTP Cat. 3, 4, 5 (100 m)
 - EIA/TIA-568 100-ohm STP (100 m)
- 100BASE-TX:
 - UTP Cat. 5 (100 m)
 - EIA/TIA-568B 100-ohm STP (100 m)

Number of Ports

10/100Mbps port x 24

Media Interface Exchange

Auto MDI-II/MDI-X for each port

Twisted-pair Rx Reverse Polarity

Auto-correction for each port

Diagnostic LEDs

- Per device:
- Power
- Per port:
- Link/Activity
 - 100Mbps speed

Performance

Transmission Method

Store-and-forward

Filtering Address Table

8K entries per device

MAC Address Learning

Automatic update

Packet Filtering Rates

- 10BASE-T: 14,880 pps per port (half-duplex)
- 100BASE-TX: 148,810 pps per port (half-duplex)

Packet Forwarding Rates

- 10BASE-T: 14,880 pps per port (half-duplex)
- 100BASE-TX: 148,810 pps per port (half-duplex)

RAM Buffer

2.5Mbits per device

Physical & Environmental

Power Supply

100 - 240 VAC, 50/60 Hz 0.3A
Internal universal power supply

Power Consumption

10 watts (max.)

Ventilation

no DC fan required

Operating Temperature

0° - 40°C

Storage Temperature

-10° - 70°C

Humidity

5% - 90%

Dimensions

280 (W) x 180 (D) x 44 (H) mm

Weight

2.8 kg

Emission (EMI)

- FCC Class A
- CE Class A
- VCCI Class A

Safety

- CUL
- CB



Ordering Information

Ethernet/Fast Ethernet Switch

DES-1024D 24 10/100Mbps ports

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.
Canada
Europe
U.K.
Germany
France
Italy
Iberia
Sweden
Norway
Denmark
Finland
Singapore
Australia
Japan
China
India
Middle East
South America
Brazil
South Africa
Russia
Taiwan
D-Link Corp.

TEL: 1-949-788-0805	FAX: 1-949-753-7033
TEL: 1-905-829-5033	FAX: 1-905-829-5095
TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
TEL: 49-61- 96779900	FAX: 49-61-967799300
TEL: 33-1-30238688	FAX: 33-1-30238689
TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
TEL: 34-93-4090770	FAX: 34-93-4910795
TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
TEL: 47-22-991890	FAX: 47-22-207039
TEL: 45-43-969040	FAX: 45-43-424347
TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
TEL: 65-6774-6233	FAX: 65-6774-6322
TEL: 61-2-9417-7100	FAX: 61-2-9417-1077
TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
TEL: 86-010-8518-2533	FAX: 86-010-8518-2250
TEL: 91-22-652-6696	FAX: 91-22-652-8914
TEL: 202-2456176	FAX: 202-2456192
TEL: 56-2-232-3185	FAX: 56-2-232-0923
TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
TEL: 27(0)126652165	FAX: 27(0)126652186
TEL: 7-095-737-3389	FAX: 7-095-737-3390
TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Aug. 2002)
Printed in Taiwan