

Managed L2 Gigabit Stack

Entry-Level SNMP Solution

- High Port Density Gigabit & PoE Stackable Switches
- Up to 4 Fiber Links Via Combo SFP
- 10-Gigabit Bi-Directional Stacking Bandwidth
- 802.1X User Authentication & ACL Access Security
- Network Protection With D-Link Safeguard Engine

FEATURES

Flexible Choices of High Port Densities

- 24 or 48 10/100/1000BASE-T Ports
- 4 Combo SFP for Fiber Gigabit and 100BASE-FX Links
- 802.3af Power Over Ethernet Support ¹

High Bandwidth Physical Stacking

- 2 HDMI Ports Per Switch
- Up to 20Gbps Full-Duplex Stacking Bandwidth
- Up to 6 Units (288 Gigabit Ports) Per Stack
- Linear or Fault Tolerant Ring Stacking Topology

Security

- Port Security
- ACL
- 802.1X Port-Based/MAC-Based Access Control
- Guest VLAN
- Traffic Segmentation
- 256 VLAN Groups
- D-Link Safeguard Engine

Traffic Monitoring/Bandwidth Control

- Port Mirroring
- Granular Bandwidth Control (Down to 64Kbps Per Port/Flow)
- Broadcast Storm Control

Resiliency/Performance

- 802.1D, 802.1w and 802.1s Spanning Tree
- 802.3ad Link Aggregation (Port Trunks)
- Trunking/Mirroring Across Multiple Units Within a Stack
- Jumbo Frames Up to 10,240 Bytes

Configuration/Management

- Web-Based GUI
- Command Line Interface (CLI)
- Telnet Client/Server
- SNMP v1, v2c, v3 & RMON v1
- RADIUS/TACACS+ Authentication for Management Access
- SSH v1, v2, SSL v3

¹ Available on DGS-3100-24P and DGS-3100-48P only.

² MLD snooping available in future firmware upgrade.

The DGS-3100 series switches are managed Layer 2 Gigabit stackable switches designed as feature-rich, low-cost devices in the entry-level network management category. These series consists of 24 and 48 port 10/100/1000Mbps switches, with or without 802.3af Power over Ethernet (PoE) support - all with up to 20Gbps physical stacking ability. Outstanding features include scalable expansion, 4 combo SFP fiber links, comprehensive network security, granular bandwidth control and extensive network management. SMB looking for a flexible, advanced but affordable solution can deploy these switches to set up Gigabit connections to their desktops or build up a company-wide network backbone.

Physical Stacking. Each of the DGS-3100 series switches comes with 2 dedicated HDMI stacking ports, each providing 5Gbps stacking bandwidth (up to 20Gbps for overall system in full-duplex mode, bi-directional). Up to 6 units, 288 10/100/1000Mbps ports can be stacked up in a linear or fault-tolerant Ring topology. A stack can consist of 10/100/1000Mbps switches, 10/100/1000Mbps PoE switches, or a combination of both types, with up to 24 SFP fiber links. Units can be gradually added to the stack to accommodate growth, while expansion beyond a single stack is possible using Gigabit port trunks between stacks, or from stack to network backbone and server paths.

Security & Availability. The DGS-3100 stack includes many security features including Access Control List (ACL), 802.1X Port-Based/MAC-Based Access Control and 802.1X Guest VLAN to make network access available to authorized users. To prevent malicious attack and virus/worm affection from overwhelming the switch with unnecessary workload, the DGS-3100 stack provides the D-Link Safeguard Engine function to increase the switch's reliability and availability.

Resilience/Performance Enhancement. To enhance network resilience, the DGS-3100 stack provides Spanning Tree protocols, including 802.1D, 802.1w and 802.1s for redundant bridge paths. 802.3ad Link Aggregation provides the aggregated bandwidth between switches or server. For Quality of Service (QoS), it supports 802.1p Priority Queues and packet classification based on TOS, DSCP, MAC, IP, VLAN ID and L4 protocol types, enabling Internet voice, video and streaming media applications to run smoothly.

Traffic Monitoring/Bandwidth Control. Network administrators can define throughput levels for each port to manage bandwidth. The bandwidth limiting feature provides fine granularity with the ability to define limits down to 64Kbps segments. Broadcast storm control and flow-based bandwidth control can reduce the level of damage that a virus attack can do to the network. The switch provides IGMP snooping and MLD snooping ² to control multicast transmission, and port mirroring to facilitate diagnostics.

Management. The DGS-3100 stack supports standard-based management protocols such as SNMP, RMON, Telnet, Web GUI and SSH/SSL security authentication. With DHCP auto-configuration, the administrator can pre-set configurations and save them in a TFTP server, and individual switches can boot their IP from the server and load in the pre-set configurations.



Hardware Specifications

DCS-3100-24

DCS-3100-24P

DCS-3100-48

DCS-3100-48P



	DCS-3100-24	DCS-3100-24P	DCS-3100-48	DCS-3100-48P
Interface				
10/100/1000BASE-T Ports	24	24	48	48
Combo SFP	4	4	4	4
RS-232 Console Port	✓	✓	✓	✓
Optional Redundant Power Supply	DPS-300	DPS-600	DPS-500	DPS-600
Stacking				
HDMI Stacking Ports	2	2	2	2
Number of Unit Per Stack (Max)	6	6	6	6
Bandwidth/Topology	Up to 10Gbps (Linear Topology) Up to 20Gbps (Bi-Directional Redundant Ring Topology)			
Power Over Ethernet				
802.3af PoE Support	-	Per 10/100/1000BASE-T Port	-	Per 10/100/1000BASE-T Port
Power Provision Per Port (Max.)	-	15.4W	-	15.4W
System PoE Power Budget	-	370W	-	370W
Auto Power/Device Discovery	-	✓	-	✓
Over-Current Protection	-	✓	-	✓
Performance				
Switch Capacity	68Gbps	68Gbps	116Gbps	116Gbps
64-Byte Packet Forwarding Rate	50.60Mpps	50.60Mpps	86.31Mpps	86.31Mpps
MAC Address Table Size	8K	8K	8K	8K
Packet Buffer	768KB	768KB	1.5MB	1.5MB
Jumbo Frame (Max.)	10,240Bytes	10,240Bytes	10,240Bytes	10,240Bytes
Physical & Environmental				
Power Input	100 to 240 VAC, 50 to 60 Hz Internal Universal Power Supply			
Power Consumption (Max)	49.39W	555.50W	102.63W	619.30W
Dimensions	440mm x 210mm x 44mm	440mm x 310mm x 44mm 19-inch Rack Mount Width, 1U Height	440mm x 310mm x 44mm 19-inch Rack Mount Width, 1U Height	440mm x 430mm x 44mm
Weight	3.04kg	5.58kg	5.50kg	7.43kg
Heat Dissipation	168.53 BTU/hr	1895.48 BTU/hr	350.19 BTU/hr	2113.18 BTU/hr
MTBF	212,377 hrs	117,136 hrs	103,924 hrs	96,648 hrs
Operating Temperature	0° to 40°C (32° to 104° F)			
Storage Temperature	-10° to 70°C (-14° to 158° F)			
Operating Humidity	10% to 90% non-condensing			
Storage Humidity	5% to 90% non-condensing			
EMI/EMC	FCC Class A, ICES-003 Class A, CE, C-Tick, VCCI Class A			
Safety	cUL, CB			

Software Functions

L2 Features

- IGMP snooping v1, v2
 - Up to 256 IGMP snooping groups
 - Up to 64 static multicast address
 - IGMP Per VLAN
 - IGMP snooping fast leave
- MLD snooping *
- Spanning Tree
 - 802.1D STP
 - 802.1w RSTP
 - 802.1s MSTP
- STP Loopback Detection
- BPDU filtering
- 802.3ad Link Aggregation: max. 32 groups per device, 8 ports per group
- Mirroring
 - One-to-one mode
 - Many-to-one mode

VLAN

- 802.1Q
- 802.1v protocol VLAN *
- VLAN Groups: total 256 VLAN groups, max. 256 static VLAN groups, max. 256 dynamic VLAN groups
- GVRP
- Double VLAN *
- Asymmetric VLAN *

ACL (Access Control List)

- Maximum Mask/Profiles: 15 profiles, 240 rules per profile
- Content-based ACL according to:
 - 802.1p priority
 - VID
 - MAC address

- Ether type
- IP address
- DSCP
- L4 Protocol type
- TCP/UDP port number
- Time Based ACL *

QoS (Quality of Service)

- Priority queues number: 4 queues
- 802.1p standard
- Queue handling: WRR/Strict/ST+WRR modes
- Bandwidth Control:
 - Port and Flow based bandwidth control
 - Granularity: down to 64Kbps
- Class of Service based on:
 - 802.1p priority
 - VLAN
 - MAC address
 - Ether type
 - IP address
 - DSCP
 - Protocol type
 - TCP/UDP port number

Security

- Traffic Segmentation
- SSH v2
- SSL v3
- Port Security: 16 MACs per port
- Broadcast storm control
- D-Link Safeguard Engine

AAA

- Port/MAC-Based 802.1X Access Control
- Guest VLAN

- RADIUS Auth. for Mgmt Access
- TACACS+ Auth. for Mgmt Access
- Web-based Access Control *
- MAC-based Access Control *

Management

- Web-based GUI
- CLI
- Device Locator
- Telnet Server
- Telnet Client
- TFTP client
- SNMP v1, v2c, v3
- SNMP Traps
- System Log
- RMON v1
- BootP/DHCP client
- DHCP Auto-configuration
- SNTP
- Port Description
- CPU Monitoring
- Web GUI Traffic Monitoring

MIB

- MIB II (RFC 1213)
- Bridge MIB (RFC 1493)
- SNMP v2 MIB (RFC 1907)
- RMON MIB (RFC 1757, 2819)
- Ether-like MIB (RFC 2021)
- 802.1p MIB (RFC 1643, 2358, 2665)
- IF MIB (RFC 2674)
- RADIUS Authentication Client MIB (RFC 2233, 2863)
- RADIUS Accounting Client MIB (RFC 2618)
- Private MIB

* Features available in future firmware upgrade

Optional Products

Optional SFP Transceivers

- DEM-310GT** (1000BASE-LX, Single-mode, 10km)
- DEM-311GT** (1000BASE-SX, Multi-mode, 500m)
- DEM-312GT2** (1000BASE-SX, Multi-mode, 2km)
- DEM-314GT** (1000BASE-LX, Single-mode, 50km)
- DEM-315GT** (1000BASE-LX, Single-mode, 80km)
- DEM-210** (100BASE-FX, Single-mode, 15km)
- DEM-211** (100BASE-FX, Multi-mode, 2km)

Optional WDM Transceivers

- DEM-330T** (1000BASE-LX, wavelength Tx: 1550nm, Rx: 1310nm, Single-mode, 10km)
- DEM-330R** (1000BASE-LX, wavelength Tx: 1310nm, Rx: 1550nm, Single-mode, 10km)
- DEM-331T** (1000BASE-LX, wavelength Tx: 1550nm, Rx: 1310nm, Single-mode, 40km)
- DEM-331R** (1000BASE-LX, wavelength Tx: 1310nm, Rx: 1550nm, Single-mode, 40km)



D-Link Worldwide Offices

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Bulgaria	TEL: 359 2 958 22 42	FAX: 359 2 958 65 57
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Romania	TEL: 40(0)21 320 23 05	FAX: 40(0)21 320 23 07
Europe (U. K.)	TEL: 44-(0)20-8955-9000	FAX: 44-(0)20-8955-9001	Singapore	TEL: 65-6774-6233	FAX: 65-6774-63225
Germany	TEL: 49-(0)6196-77990	FAX: 49-(0)6196-7799300	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
France	TEL: 33 (0)1 30 23 86 88	FAX: 33 (0)1 30 23 86 89	India	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914
Netherlands	TEL: 31-(0)10-282-1445	FAX: 31-(0)10-282-1331	Middle East (Dubai)	TEL: 971-4-391-6480	FAX: 971-4-390-8881
Belgium & Luxembourg	TEL: 32(0)2 517 7111	FAX: 32(0)2 517 6500	Egypt	TEL: 202-291-9035	FAX: 202-291-9051
Switzerland	TEL: 41 (0)1 832 11 00	FAX: 41 (0)1 832 11 01	Turkey	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Austria	TEL: 43 (0)1 240 27 270	FAX: 43 (0)1 240 27 271	Iran	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Sweden	TEL: 46-(0)8 564 619 00	FAX: 46-(0)8 564 619 01	Pakistan	TEL: 92-21-454-8158	FAX: 92-21-453-5103
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47 99 300 100	FAX: 47 22 30 90 85	Latin America	TEL: 56-2-5838-950	FAX: 56-2-5838953
Finland	TEL: 358-10 309 8840	FAX: 358-10 309 8841	Brazil	TEL: 55-11-2185-9300	FAX: 55-11-2185-9322
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Spain	TEL: 34 93 409 0770	FAX: 34 93 491 0795	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099
Portugal	TEL: 351 21 8688493	FAX: 351 21 8622492	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Greece	TEL: 30 210 9914 512	FAX: 30 210 9916902	Korea	TEL: 82-2-890-5491	FAX: 82-2-890-549
Czech Republic	TEL: 420 224 247 500	FAX: 420 224 234 967	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Hungary	TEL: 36 (0)1 461 30 00	FAX: 36 (0)1 461 30 04	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-3939
Poland	TEL: 48 (0)22 583 92 75	FAX: 48 (0)22 583 92 76	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898