



SRT96RMBP



Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: Rack Mounting brackets, User Manual, Warranty card

Technical Specifications

Output

Battery Output Voltage	96V
-------------------------------	-----

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	--
Expected Battery Life (years)	3 - 5
RBC Quantity	2

Physical

Maximum Height	85MM, 8.5CM
Maximum Width	432MM, 43.2CM
Maximum Depth	594MM, 59.4CM
Rack Height	2U
Net Weight	40.6KG
Shipping weight	44.5KG
Shipping Height	239MM, 23.9CM
Shipping Width	599MM, 59.9CM
Shipping Depth	831MM, 83.1CM
Color	Black
Units per Pallet	6.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (no %)
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (no %)
Storage Elevation	0-15000meters

[Back to top](#)



Conformance

Approvals	OSHPD
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Proposition 65 Warning	Available in Documentation tab

Recently viewed



APC Smart-UPS C 1000VA
LCD RM 2U 230V
SMC1000I-2U

[Back to top](#)

