

Juniper SFP-FE20KT13R15 Compatible SFP Transceiver Module - 100Base-BX10-U (Upstream)

Product ID: SFPFE20KT3R5



The SFPFE20KT3R5 is a Juniper SFP-GE10KT14R13 compatible fiber transceiver module that has been designed, programmed and tested to work with Juniper brand switches and routers. It delivers dependable 100 MbE connectivity over fiber cable, for 100Base-BX10-U compliant networks, with a maximum distance of up to 20 km (12.4 mi).

Technical Specifications:

- **Wavelength:** 1310nmTx/1550nmRx
- **Maximum Data Transfer Rate:** 100 Mbps
- **Type:** Single Mode Fiber
- **Connection Type:** LC Connector
- **Maximum Transfer Distance:** 20 km (12.4 mi)
- **MTBF:** 3,713,222 hours
- **Power Consumption:** Low power consumption
- **Digital Diagnostics Monitoring (DDM):** Yes

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

**Certifications, Reports
and Compatibility**



Features

- 100% Compatibility with Juniper SFP-FE20KT13R15 guaranteed
- Backed by a 3-year warranty
- Meets or exceeds OEM specifications and Multi-Source Agreement (MSA) industry standards
- Low power consumption
- Hot-swappable with fiber-optic modules

Hardware	Warranty	Lifetime
	Compatible Brand	Juniper®
Performance	Compatible Networks	100 Mbps
	DDM	Yes
	Maximum Data Transfer Rate	100 Mbps
	Wavelength	1310nmTx/1550nmRx
Physical Characteristics	Product Height	0.5 in [1.2 cm]
	Product Length	2.6 in [65 mm]
	Product Width	0.6 in [14 mm]
	Weight of Product	2.5 oz [72 g]
Packaging Information	Package Height	0.6 in [15 mm]
	Package Length	9.1 in [230 mm]
	Package Width	8.1 in [207 mm]
	Shipping (Package) Weight	2.8 oz [80 g]
What's in the Box	Included in Package	1 - SFP Transceiver
	Fiber Operating Mode	Full-Duplex
	Max Transfer Distance	20 km (12.4 mi)

Product appearance and specifications are subject to change without notice.