



The lightest and most compact mobile printer

RJ-2035B





Lightweight and Compact

At only 215g and so small that it almost fits in the palm of your hand, there's no need for extra space to accommodate this new addition into your kit of work devices.



Reliable Connectivity

Provides multiple connectivity options for use in different environments, with USB, Bluetooth (low energy) with MFI capabilities and passive NFC.



Robust Design

The RJ-2035B has an IP42 rating and drop tested up to 1.8 metres, providing extensive durability.



Seamless Integration

Printer drivers are available for Windows, Mac and Linux and Software Development Kits (SDK's) can be downloaded to support Android and iOS operating systems.



Customisation

We have a wide range of accessories made to suit any environment. See next page.

The RJ-2035B mobile receipt printer is ideal for printing receipts in any point of service location.

Lightweight and compact, this 2" receipt printer has a range of connectivity options and integrates easily into your existing systems thanks to the supported printer command languages and free of charge Software Development Kits (SDK's)



Warehouse

Delivery Reports

Industries we serve

Designed to meet the needs of specialist business sectors



Logistics & **Deliveries**

Invoicing



Ticketing

Parking Notice Parking Fine



Field Sales and Service

Retail

Point of Sale mobile receipts

Receipts

Customise your solution

Brother has designed and engineered a wide range of accessories to meet your specific requirement for a customised solution and are available to enhance your workflow for both in-vehicle and on-body applications.

Power options & accessories



PA-BT-008 2" Li-ion battery



PA-CR-003 2" 1-bay cradle charger



PA-CD-001CG Car adapter



PA-SS-001 Shoulder strap



PA-4BC-001 2" 4-bay battery charger

Technical Specifications for the RJ-2035B Direct Thermal Printing technology Print resolution 203dpi Maximum 101.6mm/second (4ips) Print speed* Maximum print width 48mm Maximum print length 2794mm Length of receipts per battery charge Li-ion battery: approx. 36m (*under Brother standard environment) Media width Max. 58mm Media types Receipts Roll diameter 30mm max Battery status x 3, Printer Status x 1, RF connection x1 1 feed/pause button and 1 power button Type USB USB version 2.0 (high speed, micro) Bluetooth Bluetooth version 5.0 Bluetooth profiles SPP (Serial Port Profile - low energy), GATT (low energy), iAP supported MFi support NFC Yes (Passive) Operating system Windows 7 / 8.1 / 10, Server 2012/R2, 2016, 2019, Mac OS 10.11 or greater, Linux deb/rpm Mobile Operating System Android, iOS Windows 7 /8 / 8.1 / 10, Android 4.0.3 or later, IOS 7.0 or later, Requires 3rd party app development using Brother SDK. Further information available at:https://www.brother.com.au/en/contents/software-development-kits Software Development Kit (SDK) availability Software Available Windows: BarTender UltraLite, Brother Printer Management Tool (BPM), Brother Comm Tool, Brother Printer Driver, OPOS Printer Driver, Seagull Driver, Mac: Printer Driver. Linux: Printer Driver, Android/iOS: Label Print for Brother (KuO) **Supported Command Language** EPL2, ZPL2, FBPL, CPCL, OPOS (Download) (Emulations) RAM 32MB Flash 16MB 1.8 metres Drop protection* Sealing Operating temperature Operating: -15°C to +50°C Charging: 0°C to +40°C Storage temperature -30°C to +70°C 2" Rechargeable Li-ion Battery (PA-BT-008) 7.4V, 1130mAh Battery (optional accessory) 2" 4-bay Battery Charger (PA-4BC-001) Battery Charger (optional accessory) Cradle Charger (optional accessory) 2" 1-bay Cradle Charger (PA-CR-003) Car adaptor (optional accessory) Car Adaptor (PC-CD-001CG) 12-24v Shoulder Strap (optional accessory) Shoulder Strap (PA-SS-001) **Dimensions** 79(w) x 116(d) x 36.5(h) Weight (with battery) 215g

Box Contents

Printer
Belt clip
Product Setup Guide
Auto-switching power adaptor
Li-ion battery







