

Technical Accessory Guides (TAGs)

For Associates, Resellers, ISVs and Alliance Partners

Global



Version: All

Will show products that are known to be available for sale and discontinued products along with suggested replacements, when known

Need to provide an update or change?

Contact <mailto:pgw786@zebra.com>



For Internal Use by
PartnerConnect Members Only



ET6X Technical Accessory Guide




NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.


* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Cradles and Charging

Cradles/Docking Stations (for Indoor use)





Part Number	Picture	Description	Notes	Required Items
STND-ET-DESK-01		Desktop Stand for Vehicle Docks	<ul style="list-style-type: none">▶ Allows Vehicle Docks to be used in desktop environments▶ Provides VESA 100x100 and VESA 75x75 hole mounting patterns.▶ Stand will tilt up-down.	




Battery Charging








Part Number	Picture	Description	Notes	Required Items
SAC-ET6X-2SCHG-01		Two-Slot Battery Charger	<ul style="list-style-type: none">▶ Charges up to 2 spare batteries.▶ Compatible with Standard or Extended Capacity batteries.▶ Uses Zebra ShareCradle design	<ul style="list-style-type: none">▶ Power Supply (PWR-BGA12V50W0WW)▶ DC Line Cord (CBL-DC-388A1-01)▶ AC Line Cord (23844-00-00F or country specific version)


Communication Cables

Part Number	Picture	Description	Notes	Required Items
-------------	---------	-------------	-------	----------------

CBA-UF6-C09ZAR		ET6X to 36xx Series Scanner Cable (USB), 9 ft.	<ul style="list-style-type: none"> ▶ Cable rated for 1.2A current ▶ Coiled cable is 9 ft long when extended and is about 5 ft. long when un-extended. ▶ Rated to -30°C for freezer environment use. ▶ When connected to STB3678/FLB3678, will charge a fully depleted battery in about 4.5 hours if host USB port is BC 1.2 compatible or about 10.5 hours for USB 2.0 host ports. ▶ ET6X's side USB port and docking stations are capable of powering DS3608-ER in default full power mode. 	
CBA-UF6-C12ZAR		ET6X to 36xx Series Scanner Cable (USB), 9 ft.	<ul style="list-style-type: none"> ▶ Cable rated for 1.2A current ▶ Coiled cable is 9 ft long when extended (even though SKU indicates 12 ft.) and is about 5 ft. long when un-extended. Use CBA-UF8-C12ZAR for a true 12 ft. length cable. ▶ Rated to -30°C for freezer environment use. ▶ When connected to STB3678/FLB3678, will charge a fully depleted battery in about 4.5 hours if host USB port is BC 1.2 compatible or about 10.5 hours for USB 2.0 host ports. ▶ ET6X's side USB port and docking stations are capable of powering DS3608-ER in default full power mode. 	
CBA-UF6-C09ZAR-KIT ▶ Discontinued 12/2023 - see PMB 11157				
CBA-UF8-C12ZAR		ET6X to 36xx Series Scanner Cable (USB), 12 ft.	<ul style="list-style-type: none"> ▶ Cable rated for 1.2A current ▶ Coiled cable is 12 ft long when extended ▶ Rated to -30°C for freezer environment use. ▶ When connected to STB3678/FLB3678, will charge a fully depleted battery in about 4.5 hours if host USB port is BC 1.2 compatible or about 10.5 hours for USB 2.0 host ports. ▶ ET6X's side USB port and docking stations are capable of powering DS3608-ER in default full power mode. 	
CBA-U61-S07ZAR		ET6X to 36xx Series Scanner Cable (USB-C Connector)	<ul style="list-style-type: none"> ▶ Connects to USB-C port on side of ET6X tablets. ▶ Cable rated for 1.2A current ▶ Straight cable is 7 ft. long. ▶ When connected to STB3678/FLB3678, will charge a fully depleted battery in about 4.5 hours if host USB port is BC 1.2 compatible or about 10.5 hours for USB 2.0 host ports. ▶ NOTE: Android units support scanners in SSI mode while connected to USB-C port. 	

P1031365-055		ZQ6/QLn Series Printer USB Cable	<ul style="list-style-type: none"> ► Connects to USB port on ET6X ► 6 ft. straight cable 	
CA1300		Screen Blanking Cable	<ul style="list-style-type: none"> ► Allows ET6X screen to turn off while vehicle is in motion for enhanced safety. ► Connects to Serial port on the Vehicle Dock ► DB9 to open wire ► Open wires are connected to user/vehicle supplied switch or relay ► Screen Blanking application on ET6X enables screen blanking feature 	Vehicle Dock (CRD-ET6X-VEHDK-CON-01 or CRD-ET6X-VEHDK-PTA-01)
Expansion Back Accessories and Attachments				
Part Number	Picture	Description	Notes	Required Items
XBK-ET6X-KCKSTD-01		Kickstand with Rotating Hand Strap	<ul style="list-style-type: none"> ► Hand Strap is adjustable and rotates +/-90 degrees providing a secure option for holding the device. ► Kickstand provides adjustable viewing angle, keeping the tablet upright for easy reading and touch while in the field and when using the Companion Keyboard. ► Folds away for mobility and to allow device to be inserted into vehicle docks. ► Compatible with standard or extended capacity batteries. ► Handstrap includes loop for storage of optional stylus when not in use. 	
SG-ET5X-RHTP1-01		Replacement Hand Strap for Kickstand with Rotating Hand Strap	<ul style="list-style-type: none"> ► Replaces the hand strap included on the Kickstand with Rotating Hand Strap. 	Kickstand with Rotating Hand Strap (XBK-ET6X-KCKSTD-01)



<p>RAM-GDS-ROTO2-ZE25U</p> <p>(3rd party) *</p> <p>https://www.rammount.com</p>		<p>RAM Roto-Mag™ 4-in-1 Handstrap with Kickstand</p> 	<ul style="list-style-type: none"> ▶ Ergonomic 4-in-1 accessory featuring an adjustable kickstand, hand strap, integrated magnets, and rotating hand grip ▶ Hand grip rotates 360-degrees and includes four built-in magnets covered with rubber for friction for mounting to flat ferromagnetic surfaces ▶ Kickstand is fully retractable when not in-use and includes rubber feet for stability 	
Soft Goods				
Part Number	Picture	Description	Notes	Required Items
SG-ET8X-HANDLE1-01		Soft Handle	<ul style="list-style-type: none"> ▶ Integrated handle attaches to the top of the tablet. ▶ Allows users to carry the tablet without the worry of dropping it. ▶ Handle is manufactured with smooth durable soft rubber, providing maximum grip without sacrificing comfort. ▶ Handle includes a stylus storage slot and tether for stylus (stylus sold separately). For best fit into storage slot, use the Long Passive ePen/Stylus (SG-ET8X-STYLUS1-01). ▶ Attaches to ET6X via fabric straps. ▶ Also includes tether point for Shoulder Strap to allow both the Soft Handle and Shoulder Strap to be used at the same time. 	<ul style="list-style-type: none"> ▶ D-Clips for Soft Handle and Shoulder Strap (SG-ET6X-DCLIPS-01)
SG-ET8X-SHLDR1-01		Shoulder Strap	<ul style="list-style-type: none"> ▶ Allows for carrying the ET6X series long distances while freeing up hands. ▶ Attaches to tablet via fabric straps or can be attached directly to Soft Handle (SG-ET8X-HANDLE1-01).  	<ul style="list-style-type: none"> ▶ D-Clips for Soft Handle and Shoulder Strap (SG-ET6X-DCLIPS-01)





SG-ET6X-DCLIPS-01		D-Clips for Soft Handle and Shoulder Strap	<ul style="list-style-type: none"> ▶ D-Clips attach to keyboard latch points on tablet. ▶ Compatible with Vehicle docks ▶ Not compatible with Companion Keyboard ▶ Includes two clips 	
-------------------	---	--	---	--






Vehicle Cradles and Holders




Powered Cradles and Holders (provides device charging and/or communication)

Part Number	Picture	Description	Notes	Required Items
CRD-ET6X-VEHDK-CON-01		Vehicle Dock	<ul style="list-style-type: none"> ▶ Dock provides quick release for fast "grab and go" transitions between the vehicle, field, and office. ▶ Barrel-style keylock provides secure vehicle docking. Includes two keys. All locks use a common key. ▶ IP66 sealing, Extreme shock, vibration and thermal shock tested – built to survive constant pounding. ▶ POGO pins on dock are heated to avoid corrosion and loss of connection. ▶ Provides two USB 2.0 ports and one powered RS232 port. USB ports are powered from the dock and require external power to operate. Each port provides max output of 2A. ▶ USB ports capable of providing enough current for DS3608-ER in default full-power mode. ▶ All ports are securely covered in the dock's compartment. ▶ Front of cradle includes LED indicator for power status and in-dock status. ▶ Supports VESA 100x100 and VESA 75x75 hole mounting patterns. ▶ Includes mounting hardware: 4 each 10-32 hex screw, washer, nylock nut. 	<ul style="list-style-type: none"> ▶ Power supply option (see Cradle/Dock Power Supplies section)

<p>CRD-ET6X-VEHDK-PTA-01</p>		<p>Vehicle Dock - with RF Pass Through Antennas</p>	<ul style="list-style-type: none"> ▶ Dock provides quick release for fast "grab and go" transitions between the vehicle, field, and office. ▶ Barrel-style keylock provides secure vehicle docking. Includes two keys. All locks use a common key. ▶ IP66 sealing, Extreme shock, vibration and thermal shock tested – built to survive constant pounding. ▶ POGO pins on dock are heated to avoid corrosion and loss of connection. ▶ Provides two USB 2.0 ports and one powered RS232 port. USB ports are powered from the dock and require external power to operate. Each port provides max output of 2A. ▶ USB ports capable of providing enough current for DS3608-ER in default full-power mode. ▶ All ports are securely covered in the dock's compartment. ▶ Front of cradle includes LED indicator for power status and in-dock status. ▶ Dock provides the following three antenna connections: <ol style="list-style-type: none"> 1) Antenna 1 - can be configured to use as cellular or WiFi antenna 2) Antenna 2 - can be configured to use as cellular or WiFi antenna 3) GPS antenna pass-through connection for improved in-vehicle signal strength and throughput <p>Antenna connections are defined using the PTA settings app on the ET6X.</p> <p>NOTE: external antennas and cables purchased separately.</p> <ul style="list-style-type: none"> ▶ Supports VESA 100x100 and VESA 75x75 hole mounting patterns. ▶ Includes mounting hardware: 4 each 10-32 hex screw, washer, nylock nut. 	<ul style="list-style-type: none"> ▶ Power supply option (see Cradle/Dock Power Supplies section) ▶ External antennas and cables - see Mobile Mark antenna options below. <div data-bbox="1230 856 1453 1035"> <p>Set Antenna For Docked</p> <ul style="list-style-type: none"> <input type="radio"/> WWAN (ANT 1)-GPS-WWAN (ANT 2) <input type="radio"/> WIFI (ANT 1)-GPS-WWAN (ANT 2) <input type="radio"/> WIFI (ANT 1)-NONE-NONE <input type="radio"/> WIFI (ANT 1)-NONE-WIFI (ANT 2) <input checked="" type="radio"/> NONE-NONE-NONE (All Internal) </div>
<p>Gamber Johnson (3rd party) *</p> <p>(various SKUs)</p> <p>http://www.gamberjohnson.com</p>		<p>Gamber Johnson SLIM series Cradles</p>	<ul style="list-style-type: none"> ▶ Cradle/Holders for ET6X for Vehicle/Forklift/Wall installations ▶ Various Cradle options: <ul style="list-style-type: none"> - Passive - holds device (no charging) - Charge and dual USB, ports provide 1.5A current while cradle is powered (can support DS3608-ER in full power mode) ▶ Keyed lock for security and theft deterrence ▶ Forward facing docking latch/release for easy one-handed operation. ▶ VESA 75 mm mounting pattern; compatible with Gamber-Johnson's Zirkona mounting products ▶ MIL-STD 810G shock/vibration, RoHS FCC, CE, and SAE J1455 crash certifications ▶ Not compatible with ET6X expansion back accessories (rotating hand strap, etc.). 	<p><u>To Power Cradle:</u></p> <p>Via vehicle:</p> <ul style="list-style-type: none"> ▶ 3rd party Lind power supply, available from Gamber Johnson for 12-32 VDC, 20-60 VDC, 72-110 VDC ▶ or bare wire config which accepts 10-40 VDC ▶ cigarette lighter adapter config <p>Via wall outlet:</p> <ul style="list-style-type: none"> ▶ 3rd party Lind AC power supply, available from Gamber Johnson



<p>ProClip (3rd party) *</p> <p>(various SKUs)</p> <p>https://www.proclipusa.com/collections/zebra</p>		<p>ProClip ET6X Cradle solutions</p> 	<ul style="list-style-type: none"> ►Cradles for ET6X Vehicle/Forklift/Wall and Desktop installations ►Cradles offer direct USB-C access to the tablet, enabling simultaneous rapid charging and high-speed data transfer under the Power Delivery (PD) 3.1 standard. ►Cradles have been rigorously tested for forklift vibration (16Gmmrs) and USB-C insertion (20K) to ensure the tablet remains securely docked and fully functional in the harshest working environments. ►Various cradle configs to support: <u>various Cradle options:</u> <ul style="list-style-type: none"> - Key Locking or Retention Lock option ►Provides access to scanner and scan buttons while in cradle. ►VESA 75 and AMPS mounting ready ►Supports foldable keyboard mount for most common keyboards (i.e. iKey) (order ProClip SKU #216261). ►NOTE: Tablet slides into cradle from left to right. Installation of the cradle will need to account for this extra needed clearance. ►If USB ports are required (i.e. for scanner & keyboard), order ProClip USB-C Hub (SKU #216418) to provide 3 USB ports. Hub is mounted on rear of cradle. 	<p><u>To charge via AC power</u></p> <ul style="list-style-type: none"> ►ProClip Wall Power Adapter with USB-C PD and USB-A Ports (#945032) <p><u>To charge in a vehicle</u></p> <ul style="list-style-type: none"> ►ProClip Cig-Plug Adapter with USB-C PD and USB-A Ports (#945031) OR ►ProClip Hard-Wired Power Supply with USB-C PD and USB-A Ports (#216406)
<p>RAM (3rd party) *</p> <p>(various SKUs)</p> <p>https://www.rammount.com</p>		<p>RAM Vehicle Cradles</p>	<ul style="list-style-type: none"> ►Cradle/Holders for ET6X for Vehicle/Forklift/Wall installations ►Compatible with devices with or without Kickstand with Rotating Hand Strap installed. ►Compatible when the optional 2-in-1 Keyboard is attached to tablet. ►Provides access to optional CAC reader attached to tablet. ►Various Cradle options: <ul style="list-style-type: none"> - Passive only (holds device) - Charge-Only - Charge and single USB option - single port (for Printer, Keyboards, mouse, scanners) - Charge and dual USB option - (for Printer, Keyboards, mouse, scanners) - Key Locking or combination lock options - Heated POGO pin connectors for use in cold temperature environments ►The USB port(s) provide 900mAh current (can power DS3608-ER in default full power mode). 	<p>►For Charging: See RAM website for power supply options.</p> <p>►For Mounting: Compatible with C and D size RAM® 4-hole AMPS and 75mm x 75mm VESA pattern bases for attaching a double socket arm; ball and socket technology allows for near-infinite adjustability</p>
Un-Powered Cradles and Holders (passive holders, no charging support)				
Part Number	Picture	Description	Notes	Required Items
<p>Gamber Johnson (3rd party) *</p> <p>(various SKUs)</p> <p>http://www.gamberjohnson.com</p>		<p>Gamber Johnson SLIM series Cradles</p>	<ul style="list-style-type: none"> ►Holds for ET6X for Vehicle/Forklift/Wall installations ►Keyed lock for security and theft deterrence ►Forward facing docking latch/release for easy one-handed operation. ►VESA 75 mm mounting pattern; compatible with Gamber-Johnson's Zirkona mounting products ►MIL-STD 810G shock/vibration, RoHS FCC, CE, and SAE J1455 crash certifications ►Not compatible with ET6X expansion back accessories (rotating hand strap, etc.). 	





RAM (3rd party) * (various SKUs) https://www.rammount.com		RAM Vehicle Cradles	<ul style="list-style-type: none"> ► Cradle/Holders for ET6X for Vehicle/Forklift/Wall installations ► Compatible with devices with or without Kickstand with Rotating Hand Strap installed. ► Compatible when the optional 2-in-1 Keyboard is attached to tablet. ► Provides access to optional CAC reader attached to tablet. 	<ul style="list-style-type: none"> ► For Mounting: Compatible with C and D size RAM® 4-hole AMPS and 75mm x 75mm VESA pattern bases for attaching a double socket arm; ball and socket technology allows for near-infinite adjustability
Vehicle Mounting Hardware and Accessories see additional mounting options in the Common Mounting Systems TAG NOTE: When using RAM Mount hardware D-size (2.25") ball mounts are recommended for use with ET6X series.				
Part Number	Picture	Description	Notes	Required Items
AN2020		External antenna for indoor/outdoor use (2.4Ghz only)	<ul style="list-style-type: none"> ► Used with Vehicle Dock with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01). ► 2.4 GHz, 802.11 b/g, 5 dBi, RPSMA connector, magnetic mount, 2.9 meter cable 	<ul style="list-style-type: none"> ► Vehicle Dock - with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01) ► RP-SMA-Female to SMA Male adapter (132171RP)
AN2010		External antenna for indoor/outdoor use Dual Band (2.4Ghz/5Ghz)	<ul style="list-style-type: none"> ► Used with Vehicle Dock with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01). ► Dual band, 802.11 a/b/g/n/ac, 2 dBi, RPSMA connector, magnetic mount, 2.9 meter cable. 	<ul style="list-style-type: none"> ► Vehicle Dock - with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01) ► RP-SMA-Female to SMA Male adapter (132171RP)
Mobile Mark (3rd party) * MGRM3-2400-1C-BLK-120 https://www.mobilemark.com		Mobile Mark WiFi Only antenna	<ul style="list-style-type: none"> ► External antenna may provide additional WiFi coverage in challenging environments. ► Antenna supports 2.4Ghz only. ► Magnetic mount can easily be installed on top of forklift cab. ► Antenna cable length is 6 ft. 	<ul style="list-style-type: none"> ► Vehicle Dock - with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01)






<p>Mobile Mark (3rd party) *</p> <p>LTMG508</p> <p>https://www.mobilemark.com</p>		<p>Mobile Mark LTMG508 series Global Cellular, WiFi, GPS External Antenna</p>	<ul style="list-style-type: none"> ► Used with Vehicle Dock with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01). ► The 5-cable LTM series antennas includes two Cellular antennas, two WiFi antennas and one GPS antenna. ► Antenna is ideal for fleet management systems that combine GPS with a broadband cellular modem as well as WiFi. ► Designed to cover all Cellular frequencies worldwide. Covers: 617-960 & 1710-6000 MHz. See ET6X pass-through antenna connector limitation below. ► Covers WiFi 2.4-2.5Ghz & 4.9-6.0GHz frequencies. ► Measures 5.5" (140 mm) in diameter with a low profile of 2.38" (60.4 mm). Takes up significantly less space than multiple antennas. ► Antenna versions available for surface mounting or magnetic mounting. ► NOTE: Due to having two WWAN antenna connectors, ET6X pass-through antennas only supports standalone 4G/5G Low Band (i.e. Low band 4G/5G Dual-connectivity - ENDC). Mid, High, Ultra-high bands are not supported. 	<ul style="list-style-type: none"> ► Vehicle Dock - with RF Pass Through Antennas (CRD-ET6X-VEHDK-PTA-01)
<p>Amphenol RF</p> <p>132171RP</p> <p>(3rd party) *</p> <p>https://www.amphenolrf.com</p>		<p>RP-SMA-Female to SMA Male adapter</p>	<ul style="list-style-type: none"> ► Required when connecting Zebra antennas (AN2010 and AN2020) to Vehicle Dock. 	
<p>RAM-D-246U</p> <p>(3rd party) *</p> <p>https://www.rammount.com</p>		<p>RAM VESA Plate Base - D size</p>	<ul style="list-style-type: none"> ► RAM D-size (2.25") ball connected to a 4.75" square plate with 4x100mm holes and 4x75mm holes in each corner. 	
<p>350025</p>		<p>RAM Forklift mounting Kit</p>	<ul style="list-style-type: none"> ► Typically used to mount ET6X Vehicle Docks to forklifts ► Includes VESA Base Plate (RAM-D-246U), Double Socket Medium 8.44" Arm (RAM-D-201U) and Clamp Base (RAM-D-247U-25) ► Uses RAM P/N RAM-D-246U, RAM-D-201U, RAM-D-247U-25 	




KT-KYBDTRAY-ET6X-01		Keyboard Support Bracket	<p>► Attaches to rear of docks and provides these hole pattern for mounting external keyboards:</p> <ul style="list-style-type: none"> - VESA 75mm x 75mm - AMPS 38mm x 30mm vertical <p>► Hole patterns for attaching to docking cradles include:</p> <ul style="list-style-type: none"> - VESA 100mm x 100mm - VESA 75mm x 75mm 	
---------------------	---	--------------------------	---	--

Misc

Part Number	Picture	Description	Notes	Required Items
400022		Screen Protector (pack of 3)	<p>► Shatter-Resistant Screen Protector Film is an anti-glare, thin protective film with a coating designed to reduce reflections and give a clear, sharp display view even in brightly-lit conditions.</p> <p>► This is an optional screen protector. Normally not included on ET6X units.</p>	
SG-ET8X-STYLUS1-01		Long Passive ePen/Stylus (Long Capacitive Pen)	<p>► Allows for a large range of pressure sensitivity, tilt detection and hover capability.</p> <p>► Uses one AAAA battery, included.</p> <p>► Pen can be tethered to tablet with Coiled Tether (SG-ET5X-SLTETR-01).</p> <p>► Does not include tether cord. Order Tether Cord (SG-ET5X-SLTETR-01) if required.</p>	




SG-STYLUS-TCX-MTL-03 (pack of 3)		Fiber Tipped Stylus	<ul style="list-style-type: none"> ▶ Black Passive Stylus with Zebra logo ▶ 5" length ▶ Heavy duty - made from stainless steel and brass. No plastic parts - real pen feel. ▶ Can be used in rain. ▶ Micro-Knit Hybrid Mesh Fiber Tip provides silent, smooth gliding use. ▶ Big improvement over rubber tipped or plastic tipped stylus. ▶ Compatible with all capacitive touch screen devices. ▶ Can be tethered to device using SG-TC5NGTC7NG-TETHR-03. 	
SG-TC7X-STYLUS1-03 (pack of 3) SG-TC5X-STYLUS-50 (pack of 50) <small>NOTE: 50-pack is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.</small>		Passive Stylus	<ul style="list-style-type: none"> ▶ Conductive Carbon-filled plastic material w/ 5mm tip ▶ Length of stylus is 3.5". ▶ Rigid plastic stylus is optimized for enterprise durability. ▶ Clip & tether point to reduce loss. 	
SG-TC7X-STYLUS-03 (pack of 3) SG-TC7X-STYLUS-06 (pack of 6) <small>NOTE: 6-pack is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.</small>		Passive Stylus Kit with Tether	<ul style="list-style-type: none"> ▶ Includes fine-pitch, capacitive Stylus (SG-TC7X-STYLUS1-03) and coiled tether (KT-TC7X-TETHR1-03) ▶ Conductive Carbon-filled plastic material w/ 5mm tip ▶ Length of stylus is 3.5". ▶ Rigid plastic stylus is optimized for enterprise durability. ▶ Clip & tether point to reduce loss. Tether to the ET6X using the attachment points on the top right or top left sides of tablet. 	
SG-ET5X-SLTETR-01		Coiled Tether for ePen Stylus	<ul style="list-style-type: none"> ▶ Used to tether the ePen (SG-ET8X-STYLUS1-01) to the tablet. ▶ Tether can be attached to the ET6X using the attachment points on the top right or top left sides of tablet. 	



SG-TC5NGTC7NG-TETHR-03 (pack of 3)		Tether for Fiber Tipped Stylus	<ul style="list-style-type: none"> ► Used to tether the Fiber Tipped Stylus (SG-STYLUS-TCX-MTL-03) to the tablet ► String type tether prevents loss of stylus. ► Tether can be attached to the ET6X using the attachment points on the top right or top left sides of tablet. ► NOTE: This tether is recommended when using Fiber Tipped Stylus (SG-STYLUS-TCX-MTL-03). Other tethers may not fit easily through the tether loop hole on the stylus. 	
SG-ET8X-PENLOOP1-01		Stylus Holder Loop	<ul style="list-style-type: none"> ► Loop attaches to the trapezoidal shaped mounting areas on right of left sides tablet. ► Compatible with docks. 	
Headset/Audio Accessories				
Wired Headsets and Audio Accessories				
Part Number	Picture	Description	Notes	Required Items
HDST-USBC-PTT1-01		PTT Headset (USB-C connector)	 <ul style="list-style-type: none"> ► For Push-To-Talk (PTT) applications. ► Compatible with Zebra PTT Express and PTT Pro. ► Connects to USB-C port on ET6X. ► Rotating earpiece allows for right or left ear configuration. ► Provides PTT button, volume up/volume down buttons. ► Cable length is 32 in. (81 cm) ► mono with microphone ► includes clip for attaching PTT button to clothing. 	

ADP-USBC-35MM1-01		USB-C to 3.5mm Adapter Cable	<ul style="list-style-type: none"> ▶ Adapter allows headsets with 3.5mm jack to connect to the ET6X's USB-C port. This is required when using PTT Express on the ET6X. ▶ Adapter provides PTT button, volume up/volume down buttons. ▶ Adapter cable length is about 2.5 ft. (78 cm). ▶ Clip on rear of adapter allows cable to be wrapped for length management. ▶ PTT button functionality tested with the following headsets: <ul style="list-style-type: none"> - HDST-35MM-PTVP-02 Both the PTT button on the headset and the adapter may be used. Other headsets with a PTT button not listed above may not work properly and their PTT button will not be detected. This includes: HDST-35MM-PTT1-01 and HDST-25MM-PTVP-01. PTT button on the adapter will need to be used instead. ▶ Allows many Google compliant 3.5mm "consumer" headphones to function as a PTT headset while still allowing the headphone's "play/call/pause" button to operate as normal. 	
HDST-35MM-PTVP-02		PTT Headset (3.5mm Locking jack)	<ul style="list-style-type: none"> ▶ For Push-To-Talk (PTT) applications. ▶ Compatible with Zebra PTT Express and PTT Pro. ▶ Uses 3.5mm rugged jack that is keyed/collared for a locking failsafe connection. NOTE: ET6X does not support this locking connection. ▶ Rotating earpiece allows for right or left ear configuration ▶ Built-in cord wrap ▶ mono with microphone ▶ includes clip for attaching PTT button to clothing. ▶ Either the PTT button on the headset or the PTT button on the required USB-C to 3.5mm Adapter (ADP-USBC-35MM1-01) can be used. ▶ Improved resistance to cleaning and sanitizing products vs. HDST-35MM-PTVP-01 	▶ USB-C to 3.5mm Adapter Cable (ADP-USBC-35MM1-01)
HDST-35MM-PTVP-01		PTT Headset (3.5mm Locking jack)	<ul style="list-style-type: none"> ▶ Discontinued 8/2023, now use HDST-35MM-PTVP-02 - see PMB 11077. ▶ For Push-To-Talk (PTT) applications. ▶ Compatible with Zebra PTT Express and PTT Pro. ▶ Uses 3.5mm rugged jack that is keyed/collared for a locking failsafe connection. NOTE: ET6X does not support this locking connection. ▶ Rotating earpiece allows for right or left ear configuration ▶ Built-in cord wrap ▶ mono with microphone ▶ includes clip for attaching PTT button to clothing. ▶ Either the PTT button on the headset or the PTT button on the required USB-C to 3.5mm Adapter (ADP-USBC-35MM1-01) can be used. 	▶ USB-C to 3.5mm Adapter Cable (ADP-USBC-35MM1-01)

Bluetooth Headsets and Audio Accessories


NOTE: Bluetooth headsets with PTT function not supported by Zebra PTT Express application. Check with Engineering to verify compatibility with Zebra PTT Pro application.




Part Number	Picture	Description	Notes	Required Items
See HS2100-HS3100 Accessories Document		HS3100 Rugged Bluetooth Headset for VDP applications	<ul style="list-style-type: none"> ► HD Voice, also known as Wide Band Audio, brings incredible audio clarity ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation tuned for VDP (voice directed picking) applications. ► Not designed for the aggressive noise cancellation required for VoIP or voice calls. Headset's send level is not tuned to satisfy VoIP or voice standards and will result with audio being quieter at the far end and delivering more noise. ► Swap batteries on the fly — without losing the Bluetooth connection ► Split-second tap-to-pair simplicity using NFC. ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene ► 15 hours of battery power 	See HS2100/HS3100 Accessories Document for headset accessories
various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * http://www.blueparrott.com		BlueParrott Bluetooth Headsets	<ul style="list-style-type: none"> ► Various Bluetooth models available with options that include: <ul style="list-style-type: none"> - Blocking out 96% of background noise - Over 24 hours of talk time - NFC Tap to Pair capable - Bluetooth wireless range capable up to 300 ft. - Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific options.	
APTT1 or APTT2 (3rd party) * https://www.aina-wireless.com/		Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	<ul style="list-style-type: none"> ► Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ► Includes clip for attaching device to clothing for lapel speaker/mic usage. ► Features several buttons which the application developers can assign to different functions. ► Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ► Device is ruggedized, MIL-STD 810G and IP67. ► Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ► Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ► Can be easily paired to mobile computer using NFC tap-to-pair. 	







<p>BTR-155 (3rd party) *</p> <p>https://www.savoxaccessories.com</p>		<p>Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)</p>	<ul style="list-style-type: none"> ▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to clothing for lapel speaker/mic usage. ▶ Rugged wireless speaker microphone IP55. ▶ Allows cable-free movement ▶ Familiar speaker microphone functions; PTT and volume buttons ▶ Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶ LED status indication ▶ High speaker volume ▶ Includes: <ul style="list-style-type: none"> - Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap 	
<p>various (3rd party) *</p> <p>http://stonemountainltd.com</p>		<p>Stone Mountain BluSkye Bluetooth Remote Speaker Mic (RSM)</p>	<ul style="list-style-type: none"> ▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Device is ruggedized, MIL-STD 810G and IP68. 	








Power Cords/Power Supplies




AC Cords and Power Supplies for connecting directly to tablet

Part Number	Picture	Description	Notes	Required Items
PWR-BGA15V45W-UC2-WW		AC Power Supply	<ul style="list-style-type: none"> ▶ Connects to USB-C port on ET6X. ▶ Output: 15V, 3A, 45W ▶ Uses IEC 320 C5 style AC Line Cord ▶ NOTE: Power Supply is not included with ET6X. Order this item if ET6X needs to be charged outside of docking stations. ▶ Please note, the previous version of AC Power Supply used on the ET8X tablet (PWR-BGA15V45W-UC-WW) is NOT compatible with the ET6X. 	AC Line Cord (450040 or region specific version)

450040 (for US) 450047 (for Australia/New Zealand) 450042 (for EU) 450041 (for UK) 50-CBL-L10-ARGGRND (for Argentina) 50-CBL-L10-BRAZIL (for Brazil) ACC-L10LINECORD-IN (for India) ACC-L10LINECORD-TW (for Taiwan) ACC-L10LINECORD-JP (for Japan) ACC-L10LINECORD-CN (for China)		AC Line Cord for Power Supply	► IEC 320 C5 style Cord	
Cradle/Dock Power Supplies				
Part Number	Picture	Description	Notes	Required Items
450020		AC Power Supply for Cradles/Docks	► Used with all ET6X powered docks. ► 14V output, 5.5 x 2.5mm barrel jack connector.	AC Line Cord (450040 or region specific version)
450040 (for US) 450047 (for Australia/New Zealand) 450042 (for EU) 450041 (for UK) 50-CBL-L10-ARGGRND (for Argentina) 50-CBL-L10-BRAZIL (for Brazil) ACC-L10LINECORD-IN (for India) ACC-L10LINECORD-TW (for Taiwan) ACC-L10LINECORD-JP (for Japan) ACC-L10LINECORD-CN (for China)		AC Line Cord for Power Supply	► IEC 320 C5 style Cord	

450143		Cigarette Lighter Adapter (CLA) to Vehicle Docks, for 12V vehicles	<ul style="list-style-type: none"> ► Typically used to connect Vehicle Docks to vehicles providing 12V power via their cigarette lighter adapter. ► 5.5 x 2.5mm barrel jack connector. ► 12-14V input 	
450019		Cigarette Lighter Adapter (CLA) to Vehicle Docks, for 12-32V vehicles	<ul style="list-style-type: none"> ► Typically used to connect Vehicle Docks to vehicles providing 24V power via their cigarette lighter adapter. ► 5.5 x 2.5mm barrel jack connector. ► 12-32V input, 13V output ► Can be converted to connect directly to vehicle power using Direct Wire Power Cable (450134). 	
450134		Direct Wire Power Cable	<ul style="list-style-type: none"> ► Used to connect Lind Cigarette Lighter Adapter (CLA) for 12-32V vehicles (450019) directly to vehicle power. ► This cable replaces the Cigarette Lighter Adapter cable included with the CLA (450019). ► Kit does not include fuse assembly since the power block on 450019 includes this. ► NOTE: If installing in freezer environment use Lind 20-60V Isolated Power Adapter (ZE12451-5538) instead. 	Lind Cigarette Lighter Adapter (CLA) for 12-32V vehicles (450019)
300039		Direct Wire Power Cable Kit to Vehicle Docks	<ul style="list-style-type: none"> ► Used to connect Vehicle Docks directly to vehicle power. ► Can connect Vehicle Docks directly to vehicles providing 12-14V power. ► Vehicles providing higher power require additional power converter (i.e. 450083 or 450084). ► Kit includes wiring and fuse assembly. ► 5.5 x 2.5mm barrel jack connector. 	Requires additional power converter if vehicle provides more than 14V (i.e. 450083 or 450084).
CBL-ET-ADPA1-1		VH10/VC8X Power Adapter Cable	<ul style="list-style-type: none"> ► Allows Docks to be powered from legacy Zebra VH10 or VC8X series power cable. ► Forklifts wired for VH10 or VC8X can be easily converted to support ET6X without re-wiring forklift. ► Length of cable is approx 5 ft. (1.5m) 	<ul style="list-style-type: none"> ► Vehicle Power DC Converter (450083) - needed to convert voltage to 13V required by ET6X. ► Direct Wire Power Cable Kit (300039)
ACC-PWRCBL01		LXE/Honeywell Power Adapter Cable	<ul style="list-style-type: none"> ► Allows Docks to be powered from legacy LXE/Honeywell power cable. ► Forklifts wired for LXE/HON VX8, VX9 VM1, VM2, and VM3 can be easily converted to support ET6X without re-wiring forklift. 	<ul style="list-style-type: none"> ► Vehicle Power DC Converter (450083) - needed to convert voltage to 13V required by ET6X. ► Direct Wire Power Cable Kit (300039)



CA1210		PS1370 Power Supply Cable	<ul style="list-style-type: none"> ► Connects vehicle power supply/battery to PS1370 Voltage Pre-Regulator. ► Cable length is 6 ft., waterproof ► Internal P/N CB000309A01 	
CBL-ET6-ADPA2-1		PS1370 to Vehicle Dock Cable	<ul style="list-style-type: none"> ► Used to connect Vehicle Docks to PS1370 External Voltage Pre-Regulator. ► Length of cable is approx 5 ft. (1.5m) 	
450083		Vehicle Power DC Converter (9-60V)	<ul style="list-style-type: none"> ► Accepts 9-60V (9A max) vehicle power and converts to 13.2V output. ► IEC 60068 Vibration, Shock, Bump, and Salt Mist tested ► NOTE: If installing in freezer environment use External Voltage Pre-Regulator (PS1370) instead. 	Direct Wire Power Cable Kit (300039)
450084		Vehicle Power DC Converter (50-150V)	<ul style="list-style-type: none"> ► Typically used with electric fork lifts. ► Accepts 50-150V (2A max) vehicle power and converts to 13.2V output. ► IEC 60068 Vibration, Shock, Bump, and Salt Mist tested 	Direct Wire Power Cable Kit (300039)
PS1370		External Voltage Pre-Regulator (19-90V)	<ul style="list-style-type: none"> ► Recommended when installing the ET6X in freezer environments where the screen heater will be in use. ► 19-90 VDC in, 15 VDC out, 90 W ► Length of pigtail cables on both sides of regulator are about 25". ► Internal P/N 1918485-001 	<ul style="list-style-type: none"> ► CA1210 (Power Supply Cable) connects vehicle power to PS1370 ► PS1370 to Vehicle Dock Cable (CBL-ET6-ADPA2-1)
CG-X (3rd party) * http://www.havis.com		Havis Charge-Guard Auto Shut-down Timer	<ul style="list-style-type: none"> ► Automatically turns mobile equipment on when vehicle engine is started. ► When engine is turned off timer can be configured to keep equipment on from 5 seconds to 18 hours. ► Will turn equipment off before pre-set time if voltage drops too low, preventing dead vehicle battery. ► Also disconnects power to equipment if over voltage condition occurs (+18V). ► Diagnostic LED helps troubleshoot voltage problems. ► Compatible with 12V vehicle systems. ► NOTE: Timer needs to be installed as the first component in the electrical circuit (prior to the power adapter). 	
Other Power Supplies				
Part Number	Picture	Description	Notes	Required Items
CBL-DC-388A1-01		DC Power Cord	<ul style="list-style-type: none"> ► Used along with Power Supply PWR-BGA12V50W0WW to power 2-Slot Battery Charger. ► Cable length is 1.8 meters 	





PWR-BGA12V50W0WW		Power Supply	<ul style="list-style-type: none"> ► Used to power 2-Slot Battery Charger ► 100-240 VAC, 12V, 4.16A, 50W ► Provides US DOE Level VI compliance for power efficiency. 	<ul style="list-style-type: none"> ► DC Line Cord (CBL-DC-388A1-01) ► AC Line Cord (23844-00-00F or country specific version)
KIT-PWR-12V50W		Power Supply Kit	<ul style="list-style-type: none"> ► Includes Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01) 	<ul style="list-style-type: none"> ► AC Line Cord (23844-00-00F or country specific version)
23844-00-00R		AC Line Cord	<ul style="list-style-type: none"> ► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries. 	

Keyboards




See External Keyboards Technical Accessory Guide (TAG) for additional keyboard options.

Part Number	Picture	Description	Notes	Required Items
KYB-ET6X-2IN1-US1-01 (US English) KYB-ET6X-2IN1-UK1-01 (UK English) KYB-ET6X-2IN1-DE1-01 (DE German) KYB-ET6X-2IN1-FR1-01 (FR French) KYB-ET6X-2IN1-ES1-01 (ES Spanish)		Companion Keyboard	<ul style="list-style-type: none"> ► Keyboard offers a 2-in-1 laptop / tablet experience providing the mobility of a tablet and notebook-style support for data-intensive tasks. ► Hinged clamshell design allows keyboard to close, protecting the tablet's screen while carrying. ► Friction hinge provides laptop-like experience - when open does not require kickstand. Opens 180° for infinite viewing adjustment. ► Includes full travel tactile feedback keyboard with 78 full-size scissor switch keys for quality notebook feel. ► Keys are backlit with user selectable primary backlight color choice. Can scroll through primary colors with function keys for quickly changing colors and backlight intensity. ► Keyboard is IP65 sealed. ► Large integrated touchpad supports two-finger and three-finger gestures. ► No need to charge the keyboard; it is powered by the tablet and communicates via bottom pin connectors on tablet. ► Keyboard closes to cover tablet display glass for added protection and convenience. ► Includes integrated handle for easy portability even with gloves. ► Keyboard can be used when the tablet is docked in Vehicle Cradles/Docks. 	

KYBD-QW-ET-S-1		QWERTY Warehouse Keyboard with USB cable	<ul style="list-style-type: none"> ►Based on the VH10 keyboard design ►12 direct Function keys with an additional 12 via shift function. ►Dimmable backlit keys. ►IP66, -30 to +50 C, condensing - for use in Freezer Applications ►Industrial keyboard controller with temperature compensation ►Meets shock/vibrations standards: EN60721-5M3, MIL810F, and Zebra internal testing standards ►Keyboard elastomer and cable are both field replaceable. ►Can be mounted on Keyboard Tray or via RAM mount. Uses AMPS hole pattern, M4 screw size. ►Includes Keyboard Cable (CBL-ET-KBUSB1-01) ►NOTE: The keyboard's built-in heaters for use in freezer or condensing environments are NOT supported with the included USB cable. Instead use KYBD-QW-VC-01 and CBL-ET-KBUSB2-01 for these environments. 	
KYBD-QW-VC-01		QWERTY Warehouse Keyboard	<ul style="list-style-type: none"> ►Based on the legacy VH10 keyboard design ►12 direct Function keys with an additional 12 via shift function. ►Dimmable backlit keys. ►IP66, -30 to +50 C, condensing - for use in Freezer Applications ►Built-in heaters and drainage system for error free operations even in heavy condensing environments ►Industrial keyboard controller with temperature compensation ►Meets shock/vibrations standards: EN60721-5M3, MIL810F, and Zebra internal testing standards. ►Keyboard elastomer and cable are both field replaceable. ►Can be mounted on Keyboard Tray (KT-KYBDTRAY-ET6X-01) or via RAM mount. Uses AMPS hole pattern, M4 screw size. 	►Standard USB Keyboard Cable for Warehouse Keyboard (CBL-ET-KBUSB1-01) or Freezer USB Keyboard Cable for Warehouse Keyboard (CBL-ET-KBUSB2-01)

KYBD-AZ-VC-01		AZERTY Warehouse Keyboard	<ul style="list-style-type: none"> ► Based on the legacy VH10 keyboard design ► 12 direct Function keys with an additional 12 via shift function. ► Dimmable backlit keys. ► IP66, -30 to +50 C, condensing - for use in Freezer Applications ► Built-in heaters and drainage system for error free operations even in heavy condensing environments ► Industrial keyboard controller with temperature compensation ► Meets shock/vibrations standards: EN60721-5M3, MIL810F, and Zebra internal testing standards ► Keyboard elastomer and cable are both field replaceable. ► Can be mounted on Keyboard Tray (KT-KYBDTRAY-ET6X-01) or via RAM mount. Uses AMPS hole pattern, M4 screw size. 	► Standard USB Keyboard Cable for Warehouse Keyboard (CBL-ET-KBUSB1-01) or Freezer USB Keyboard Cable for Warehouse Keyboard (CBL-ET-KBUSB2-01)
CBL-ET-KBUSB1-01		Standard USB Keyboard Cable for Warehouse Keyboard	<ul style="list-style-type: none"> ► Used with Warehouse style keyboards ► Has standard USB-A connector which can be used with Vehicle docks or other devices with standard USB-A ports. ► Medium Cable length (34 cm / approx. 13.5 in) ► Typically used when keyboard is mounted directly near the device (i.e. on Keyboard Tray). ► NOTE: Cable is <u>not</u> capable of powering the keyboard's built-in heater. 	
CBL-ET-KBUSB2-01		Freezer USB Keyboard Cable for Warehouse Keyboard	<ul style="list-style-type: none"> ► Used with Warehouse style keyboards in freezer environments. ► Has standard USB-A connector and RS232 connector. RS232 connects to powered RS232 port on Vehicle Docks to provide extra power for heating the keyboard in freezer environments. ► Cable length is 29 cm / approx. 11 in ► Typically used when keyboard is mounted directly near the device (i.e. on Keyboard Tray). 	
various		Other Keyboard options	See External Keyboards Technical Accessory Guide (TAG) for other keyboard options.	

Batteries

Part Number	Picture	Description	Notes	Required Items
BTRY-ET6XA-9AH-01		Standard Capacity Replacement Battery (9.3 AHr)	<ul style="list-style-type: none"> ► This is the main battery that attaches to the back of the Android ET6X series. ► Hot swappable enables 24x7 usage. ► 9.3 AHr Lithium-ion battery keeps tablet powered for up to 10 hours. 	
BTRY-ET6XA-18AH-01		Extended Capacity Replacement Battery (18.7 AHr)	<ul style="list-style-type: none"> ► This is the main battery that attaches to the back of the Android ET6X series. ► Hot swappable enables 24x7 usage. ► 18.7 AHr Lithium-ion battery keeps tablet powered for up to 20 hours. 	
BTRY-ET6X-0AH-01		No Cell Battery (battery eliminator)	<ul style="list-style-type: none"> ► Replaces battery when the tablet will always be powered externally (i.e. in Vehicle Dock) 	<ul style="list-style-type: none"> ► Requires powered dock. Tablet can't be powered via USB-C port power with this battery.